
ELEC 3300 – Tutorial for LAB5

Department of Electronic and Computer Engineering
HKUST

by WU Chi Hang 

Terminology


ADC : analog to digital conversion

Analogue



Digital



The whole analogue range that you want to chop into



How many levels depends on the number of bits used.



L - 16 bits R - 16 bits

Nyquist rate
 $20\text{kHz} * 2$
 $= 40\text{kHz}$

sampling rate = 44.1kHz


why not higher?

because human hearing range

20 - 20kHz



An N-bit Linear DAC/ADC



Digital to Analogue Converter (DAC)

DAC: need setting time

Digital to Analog




FIGURE 10-14 Simple 4-bit D/A converter.

takes time = setting time

$$D_0 + D_1 = 3V$$

negative feedback summing amplifier

Terminology

- Resolution
 - Number of bits in the binary word used in the sample.
- Full Scale Output Voltage (for DAC)
 - Maximum output voltage of the D/A convertor. (Always 1 LSB below the stated value)
- Setting Time (for DAC)
 - When you change a binary word applied to the input of a converter, the output will change to appropriate new value. (Time the output takes to get within $\pm \frac{1}{2}$ LSB)
- Conversion Time (for ADC)
 - Time that convertor takes to produce a valid output binary code for an applied input voltage.

challenge (compro 12 \rightarrow Binary search \rightarrow 8 bit \leftarrow after 8 comparison I get my result.)
ADC \Rightarrow successive-approximation

Analogue to Digital Converter (ADC) 8614




FIGURE 10-20 Successive-approximation A/D converter circuit.

Analogue to Digital Convertor (ADC)

- In STM32 there are three ADCs inside. Each ADC is 12-bit. It has up to 18 multiplexed channels allowing it measure signals from 16 external and two internal sources.
- A/D conversion of the various channels can be performed in single, continuous, scan or discontinuous mode.
- The result of the ADC is stored in a left-aligned or right-aligned 16-bit data register.
- The conversion time is around $1\mu\text{s}$ (refer to page 207 of the reference manual)

$$T = \frac{1}{f} = f = \frac{1}{1\mu\text{s}}$$

can be used as
a CD ripper


$$f_{eq} = 1\text{MHz} > 44.1\text{kHz}$$

About Conversion Mode


- A/D conversion of the various channels can be performed in single, continuous, scan or discontinuous mode.
 - Single conversion mode
 - ADC does one conversion, after finished conversion, ADC stopped.
 - Continuous conversion mode
 - ADC starts another conversion as soon as it finishes one.
 - Scan mode
 - This mode is used to scan a group of analog channels. A single conversion is performed for each channel of the group. After each end of conversion the next channel of the group is converted automatically.
 - When using scan mode, DMA bit must be set and the direct memory access controller is used to transfer the converted data of regular group channels to SRAM after each update of the ADC_DR register.
 - Please refer to Reference Manual Section 11.3 for details.
-

About Conversion Mode

Single Channel
Single Conversion Mode




Single Channel
Continuous Conversion Mode




Scan mode


Multi-channel
Single Conversion Mode




Multi-channel
Continuous Conversion Mode



Block Diagram (Ref. Man. P. 208)



Clock Tree



Where is the ADCCLK source ? APB1/APB2 ?

What is the Max value of ADCCLK ?

Note on ADCCLK

Refer to Page 207 of the Reference Manual, it said

- ADC conversion time:

- STM32F103xx performance line devices: 1 μ s at 56 MHz (1.17 μ s at 72 MHz)

- Question

- Why the SYSCLK faster, but conversion time is longer?

Ans: ADC Prescaler

Refer to last page.

- ADCCLK originates from APB2
- The Prescaler of ADCCLK can only be /2, 4, 6, 8
- If APB2 = 72MHz, what the max ADCCLK can be ?
- If APB2 = 56MHz, what the max ADCCLK can be ?

$$72\text{MHz} / 6 = 12\text{MHz}$$

$$56\text{MHz} / 6 = 9.33\text{MHz}$$

Total Conversion Time

Refer to Section 11.6 of the Reference Manual.

- Each channel can be sampled with a different sample time.
- The total conversion time is calculated as follows:
 - $T_{\text{conv}} = \text{Sampling time} + 12.5 \text{ cycles}$ → fixed (time during conversion)
- The sampling time can be set via the SMP[2:0] bits in the ADC_SMPR1 and ADC_SMPR2 registers.
- Example:
- With an ADCCLK = 14 MHz and a sampling time of 1.5 cycles:
 - $T_{\text{conv}} = 1.5 + 12.5 = 14 \text{ cycles} = 1 \mu\text{s}$

→ can be programmed

Sampling Time

11.12.4 ADC sample time register 1 (ADC_SMPR1)

Address offset: 0x0C

Reset value: 0x0000 0000

31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16
Reserved								SMP17[2:0]			SMP16[2:0]			SMP15[2:1]	
								rw	rw	rw	rw	rw	rw	rw	rw
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
SMP15_0	SMP14[2:0]			SMP13[2:0]			SMP12[2:0]			SMP11[2:0]			SMP10[2:0]		
rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw	rw

Bits 31:24 Reserved, must be kept at reset value.

Bits 23:0 **SMPx[2:0]:** Channel x Sample time selection

These bits are written by software to select the sample time individually for each channel. During sample cycles channel selection bits must remain unchanged.

000: 1.5 cycles

001: 7.5 cycles

010: 13.5 cycles

011: 28.5 cycles

100: 41.5 cycles

101: 55.5 cycles

110: 71.5 cycles

111: 239.5 cycles

Note: ADC1 analog Channel16 and Channel 17 are internally connected to the temperature sensor and to V_{REFINT} , respectively.

ADC2 analog input Channel16 and Channel17 are internally connected to V_{SS} .

ADC3 analog inputs Channel14, Channel15, Channel16 and Channel17 are connected to V_{SS} .

Handwritten calculation:

$$1.5 + 12.5 = 14 \text{ cycles}$$

$$\frac{14}{14 \text{ MHz}} = 1 \mu\text{s}$$

About Data Alignment

- The data alignment means how the ADC data is being put into the register.

Figure 27. Right alignment of data






Figure 28. Left alignment of data



ADC in MINI-V3


- In MINI-V3, there are different ADC channels located at position 1 of the figure below




ADC in MINI-V3

- The corresponding schematic is also shown here, note that it is not pin to pin correspondence to the board.

ON BOARD VR




Note: PC0 has a 4.7kΩ to 3V3



ADC in MINI-V3

- The on board VR is not good to use and easy to be damaged. As a result, we will use an outside circuit to connect the analogue input to one of the channels



- Actually there are many ADC channels (not limited to the one shown above) in STM32 that you can use.

ADC in STM32

- Refer to STM32 Datasheet,
 - ❑ ADC1 and ADC2 have 16 channels (from IN0 to IN15) to use
 - ❑ ADC3 have 13 channels (from IN0 to IN8, IN10 to IN13)

	IN0	IN1	IN2	IN3	IN4	IN5	IN6	IN7	IN8	IN9	IN10	IN11	IN12	IN13	IN14	IN15
ADC1																
ADC2																
ADC3										N/A					N/A	N/A

- In Datasheet
 - ❑ ADC123_IN10 → means Channel 10 shared by ADC1 ADC2 and ADC3
 - ❑ ADC12_IN5 → means Channel 5 shared by ADC1 and ADC2 only
 - ❑ ADC3_IN8 → means Channel 8 for ADC3 only
- Question : If one shared channel means one I/O pin, if we use all the channels available, how many I/O pins will be used by ADC ?



Ans: 21

ADC in STM32

20654091

- In this LAB, we will use **ADC1** only, you need to use the channel according to the last digit of your student ID

Last digit of your student ID	0	1	2	3	4	5	6	7	8	9
Channel number	12	13	2	3	4	5	6	7	14	15
Corresponding I/O pin in STM32 ? 🤔										


- Check the corresponding I/O pin from datasheet then check the location of that pin on MINI V3 board



1 = ADC123 - IN13 ⇒ PC3

Using VR as input

- Using your breadboard, assemble the following circuit, this would be used for your Task 1 and Task 2.




Configuration of LCD

- In this LAB, we need to use the LCD to display the value.
- Please refer to the Tutorial for CubeMX and Tutorial for LAB3 to create a project that allows you to use the LCD Display.
- Or you may start your LAB5 by using the LAB3 as a starting point.


Set Clock

- You will go to this screen, first we need to set the clock, Expand System Core




Change Clock to Crystal

- Click RCC, enable the High Speed Clock and Low Speed Clock to
 - ❑ Crystal/Ceramic Resonator




Clock Configuration


- Go to Clock Configuration



Clock Configuration



Setting the clock of ADC in CubeMX



- Is it the fastest setting of ADCCLK?
- How can you change it to fastest ?

N^o
🤔 56MHz

Configuration of ADC

The screenshot shows the STM32CubeMX configuration interface. The left sidebar has a tree view with 'System Core' expanded, showing 'DMA', 'GPIO', 'IWDG', 'NVIC', 'RCC', 'SYS', and 'WWDG'. Under 'Analog', 'ADC1' is selected and highlighted with a red box. The main panel is titled 'ADC1 Mode and Configuration'. It has tabs for 'Mode', 'Configuration', 'Parameter Settings', 'User Constants', 'NVIC Settings', 'DMA Settings', and 'GPIO Settings'. The 'Mode' tab is active, showing a list of channels: IN12, IN13, IN14 (checked and highlighted with a red box), and IN15. A red text label 'Channel number you use' points to IN14. Below the channel list is the 'Configuration' section. It has a 'Reset Configuration' button and tabs for 'Parameter Settings', 'User Constants', 'NVIC Settings', 'DMA Settings', and 'GPIO Settings'. The 'Parameter Settings' tab is active, showing a search bar and a list of parameters. The 'ADCs_Common_Settings' section is expanded, showing 'Mode' (Independent mode), 'Data Alignment' (Right alignment), 'Scan Conversion Mode' (Disabled), 'Continuous Conversion Mode' (Disabled), and 'Discontinuous Conversion Mode' (Disabled). The 'ADC_Regular_ConversionMode' section is expanded, showing 'Enable Regular Conversions' (Enabled), 'Number Of Conversion' (1), and 'External Trigger Conversion Source' (Regular Conversion launched by software). The 'Rank' section is expanded, showing 'Channel' (Channel 14), 'Sampling Time' (55.5 Cycles), and 'Number Of Conversions' (0). A red box highlights the 'Rank' section, and a red text label 'Conversion Selection' points to it. A handwritten pink note '+12.5) x 12 MHz' is written next to the 'Sampling Time' value.

Pinout & Configuration

Clock Configuration

Additional Software

Pinout

Categories A-Z

System Core

DMA

GPIO

IWDG

NVIC

✓ RCC

✓ SYS

WWDG

Analog

ADC1

ADC2

ADC3

DAC

Timers

Connectivity

CAN

FSMC

I2C1

I2C2

SDIO

SPI1

SPI2

SPI3

UART4

UART5

USART1

ADC1 Mode and Configuration

Mode

IN12

IN13

IN14

IN15

Temperature Sensor Channel

Vrefint Channel

Configuration

Reset Configuration

Parameter Settings

User Constants

NVIC Settings

DMA Settings

GPIO Settings

Configure the below parameters :

Search (Ctrl+F)

ADCs_Common_Settings

Mode

Independent mode

Data Alignment

Right alignment

Scan Conversion Mode

Disabled

Continuous Conversion Mode

Disabled

Discontinuous Conversion Mode

Disabled

ADC_Regular_ConversionMode

Enable Regular Conversions

Enabled

Number Of Conversion

1

External Trigger Conversion Source

Regular Conversion launched by software

Rank

Channel

Channel 14

Sampling Time

55.5 Cycles

Number Of Conversions

0

ADC_Injected_ConversionMode

Number Of Conversions

0

WatchDog

Enable Analog WatchDog Mode

Disabled

Channel number you use


Mode and Alignment Selection

Conversion Selection

+12.5) x 12 MHz

Communicate with Debugger

- Go to Pinout & Configuration, in SYS, Choose Serial Wire for Debug



About Calibration

- The ADC has an built-in self calibration mode. Calibration significantly reduces accuracy errors due to internal capacitor bank variations.
- During calibration, an error-correction code (digital word) is calculated for each capacitor, and during all subsequent conversions, the error contribution of each capacitor is removed using this code.
- Once calibration is over, the CAL bit is reset by hardware and normal conversion can be performed. It is recommended to calibrate the ADC once at power-on. The calibration codes are stored in the ADC_DR as soon as the calibration phase ends.

About Calibration

- The datasheet suggested to perform a self calibration at the startup, so, you may want to add the following line before the while(1) loop of your code.

```
HAL_ADCEx_Calibration_Start(&hadcl);
```

Depends on which ADC you use

How to start a conversion and get the result ?

- The ADC conversion can be initiated by

```
HAL_ADC_Start(&hadc1);
```

- Please note that there is a time needed for the conversion, you can use the following line to poll the end of conversion.

```
HAL_ADC_PollForConversion(&hadc1, 1000);
```


Timeout in milliseconds

- You can read the conversion result by calling the procedure

```
uint32_t HAL_ADC_GetValue(&hadc1);
```

Task 1 – Single Conversion

- You need to write a program to display an ADC conversion result of the external VR in both decimal and hex. The converted value will be updated when K2 is pressed.
- You are required to use **Single Conversion Mode** of ADC to finish Task 1
- You need to show to your TA your main.c for verifying the mode used



Task 1 – Display the Result


- You need to think about how to decompose the value to display. The following functions and table might help you. Details refer back to lcd.c in the lcd.zip

```
void LCD_DrawChar(uint16_t usC, uint16_t usP, uint8_t cChar);  
void LCD_DrawString(uint16_t usC, uint16_t usP, uint8_t * pStr);
```

- You can also use stdlib function like sprintf() to help you.

Task 2 – Continuous Conversion

- Change your program such that the LCD will be able to update the ADC result for **the external VR** at a certain period without pressing K2.
- You are required to use **Continuous Conversion Mode** of ADC to finish Task 2.
- You need to show to your TA your main.c for verifying the mode used



Task 1 and 2 – Note

The result you displayed should be

1. From _____ to _____ for DEC
2. From _____ to _____ for HEX
3. 1 and 2 should be **SAME** value but
DIFFERENT REPRESENTATION ONLY

If there exists (\exists) a result violating **any of above 3 conditions**, it means your program have BUG.



Please think out why 🤔and FIX it.



DEC	HEX	Correct ?
0	000	
10	0a0	
0004	000	
1234	4d2	
6007	258	
7129	2c8	



Connecting to LDR

- Light Dependent Resistor is a resistor that the resistance will depends on the light intensity. In this part, you need to use the LDR as an analogue input to the system.



Using LDR as input

- Replace your VR with a fixed resistor and a LDR



Task 3: Using LDR as input

- Following the steps listed on the LAB Sheet, fill the corresponding data.
- You might need to try to swap the LDR and the resistor.

Task 4: Light Intensity System

- Using your knowledge from Task 3 and LAB2, together with the RGB LED on MINI V3 Development Board, implement a five-level Light Intensity System such that..

	Light Intensity				
	Very Dark	Dark	Medium	Bright	Very Bright
RGB LED COLOR	WHITE	RED	GREEN	BLUE	OFF

- You can use either Figure 1 or Figure 2 on Page 2 of the LAB sheet to implement the system, as long as it follows above requirement.
- You are free to choose the boundary for the system, but you need to clearly show the TA the five different levels according to the above requirement during the demo.

END